

DRY POWDER FIRE EXTINGUISHERS (UL LISTED)

PRODUCT DESCRIPTION

NAFFCO stored pressure type dry powder extinguishers are characterised by their high performance, simple method of operation and rapid fire knock down capability. They are suitable for tackling fires involving freely burning materials, petrol, oil, gas

and electrical equipment. They are ideal for vehicle & marine risks. NAFFCO ABC powder extinguishers contain high performance powder and are one of the most powerful powder extinguishers in the world.



FEATURES

- ABC Dry Chemical is a multipurpose extinguishing agent that is suitable for use on Class A, Class B and Class C fires.
- Durable Extruded Brass Valve with Chrome Plated
- Deep-draw Cylinder with High Tensile Strength
- High Performance Dry Chemical Powder
- 100% Helium Leak Detected.
- Production Under ISO9001 Quality System

TYPICAL USES

- For public areas such as offices, classrooms, parking garages, and hotel/motel assembly halls and guest areas. For businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/ aircraft/ marine service centers, and manufacturing processes such as painting, dipping, and coating.
- Not suitable for use on fires involving cooking oil and grease. Not recommended for use on sensitive electronic equipment or aircraft structure.

Model Number	NP 2.5L	NP 05L	NP 10L	NP 20L
Agent Capacity	2.5 lb. (1.13 Kg)	5 lb. (2.27 Kg)	10 lb. (4.54 Kg)	20 lb. (9.07 Kg)
UL Rating	1-A:10-B:C	3-A:30-B:C	4-A:60-B:C	6-A:80-B:C
Discharge Time	10 Sec	14 Sec	20 Sec	30 Sec
Range (FT/M)	11 / 3.4	14 / 4.3	20 / 6.1	22 / 6.7
Operating Pressure	195 psi (13.4 Bar)			
Operating Temperature	-40°C ~ +49°C			
Bracket	Wall			
Cylinder Diameter	86 mm	113 mm	135 mm	183 mm
Extinguisher Weight	2.23 Kg	4.44 Kg	7.63 Kg	13.86 Kg
Packing Size (L x W x H) (mm)	95 x 150 x 380	120 x 170 x 460	150 x 180 x 530	210 x 190 x 620

*Head valve available with "Brass and Aluminum" Specify at the time of order

CO₂ PORTABLE FIRE EXTINGUISHERS (UL LISTED)

PRODUCT DESCRIPTION

NAFFCO CO₂ gas extinguishers are characterised by their high performance for fires including items at risk for electrical shorts like computer, office equipment and generators etc. CO₂ is non

conductive, clean and safe, ensuring minimal damage to electrical equipment and furnishings. Suitable for Class B fire risks.



FEATURES

- Carbon Dioxide is the trusted non-conductive cleaning agent and is most effective for dealing with electronic equipment fires. CO₂ is suitable for use on Class B and Class C fires.
- **TYPICAL USES:** For protecting sensitive electronic equipment in offices, classrooms, parking garages, and hotel/motel assembly halls and guest areas. For protecting sensitive

electronic equipment in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

- Not suitable for use on fires involving cooking oil and grease. Recommended for use on sensitive electronic equipment.

Model Number	N 05LC	N 10LC	N 15LC	N 20LC
Agent Capacity	5 lb. (2.27 kg)	10 lb. (4.54 kg)	15 lb. (6.8 kg)	20 lb. (9.07 kg)
UL Rating	5-B:C	10-B:C	10-B:C	10-B:C
Discharge Time	9 sec	9 sec	15 sec	20 sec
Range (FT/M)	4-8 / 1.2-2.4	4-8 / 1.2-2.4	4-8 / 1.2-2.4	4-8 / 1.2-2.4
Bracket	Wall	Wall	Wall	Wall
Ship Weight	13.75 lb. (6.3 kg)	27.75 lb. (12.6 kg)	37.75 lb. (17.1 kg)	49 lb. (22.2 kg)
Unit Height	17.375 in (44.1 cm)	19.75 in (50.2 cm)	26.375 in (67 cm)	26.875 in (68.2 cm)
Unit Width	8.25 in (21 cm)	12 in (30.5 cm)	12 in (30.5 cm)	13 in (33 cm)
Unit Diameter	5.25 in (13.3 cm)	6.89 in (17.5 cm)	6.89 in (17.5 cm)	8 in (20.3 cm)
Cylinder Material	Aluminium			