



Amerex Corporation

7595 Gadsden Hwy. Trussville, AL 35173 ♦ Ph: (205) 655-3271 ♦ Fax: 1-800-654-5980 ♦ e-mail: sales@amerex-fire.com

Model 775 150 LB. 3M™ Novec 1230™ WHEELED FIRE EXTINGUISHER



- Environmentally friendly 3M™ Novec 1230™ Clean Agent (0 ODP - 1 GWP)
- Brass, chrome plated operating valve
- 125 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Lunette coupler for towing
- Quick release 40 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Corrosion resistant lime/yellow polyurethane paint finish
- Large color coded mylar instruction labels
- Aluminum UL label with barcoded serial numbers
- Operating temperature range: -40° to +120° F.
- 6 year manufacturer's warranty

SPECIFICATIONS		150 LB. Novec 1230™
Model Number		775
Agent		Novec 1230™
Capacity (lbs.)		150
UL Rating		3A:80B:C
Shipping Weight (lbs.)		375 (filled)
Discharge Time (sec.)		22
Cylinder - DOT 4BW240		
Operating Press (psi)		125
Test Pressure (psi)		480
Burst Pressure (minimum - psi)		960
Discharge Range (ft.)		30
Hose Length (ft.)		40
Hose Diameter (in.)		1.0
Wheels (Semi-pneumatic) (in.)		16 x 4
Height (in.)		59
Width (in.)		29
Depth (in.)		42

* Model 776 available with 36" rubberized wheels